

## WILDCAT+ 640 SERIES

- High resolution SWIR imaging camera with CL or USB3 Vision interface
- 640x512 pixels
- 20  $\mu\text{m}$  pixel pitch
- USB3 Vision, CameraLink



### HIGH-RESOLUTION, SWIR CAMERA

The Wildcat+ 640 series is based upon a state-of-the-art InGaAs detector with 640x512 pixels and 20  $\mu\text{m}$  pixel pitch. The camera offers superior, high resolution SWIR imaging capabilities, comes in a versatile and industry-proven Wildcat camera package (GenICam compliant) and offers advanced on-board image processing.

The Wildcat+ 640 camera outputs full frame images up to 300 Hz via either a CameraLink or USB3 Vision interface.

### DESIGNED FOR USE IN


- Semiconductor chip and solar wafer inspection
- Scientific & Advanced Research
- Display inspection - mobile phone & TV
- Microscopy
- Laser beam analysis

### ADVANTAGES

- Compact and industry-proven camera design
- High-resolution SWIR imaging
- Advanced on-board image processing performance
- GenICam compliant
- Flexible optical mount and lens options



Art inspection



Food inspection



Semiconductor inspection

## SPECIFICATIONS

| Camera Specifications                                      | Wildcat+ 640 CL 300   | Wildcat+ 640 U3V 300  |
|--|---|---|
| Mechanical specifications                                  |   |   |
| Camera dimensions (width x height x length) [mm] (approx.) | 55 x 55 x 72  | 55 x 55 x 91.5  |
| Optical interface  | C-mount or M42  |   |
| Camera weight [gr]   | 316   | 358   |
| Connector USB  | NA  | USB 3.0 type micro-B  |
| Connector CameraLink                                       | Standard SDR  | NA  |
| Connector power  | Lemo 1B.308 (unified connector)   |   |
| Connector trigger  | Lemo 1B.308 (unified connector)   |   |
| Connector general I/O                                      | Lemo 1B.308 (unified connector)   |   |
| Environmental & power specifications                       |   |   |
| Operating temperature range (housing temperature) [°C]     | From -40 to +70   |   |
| Storage temperature [°C]                                   | From -40 to +85   |   |
| Power consumption [W]                                      | <7  |   |
| Power supply voltage                                       | DC 12 V   |   |
| Shock  | 40g, 11ms, according to MIL-STD810G   |   |
| Vibration  | 5g (20 to 2000 Hz), according to MIL-STD810G                                  |   |
| IP rating  | IP40  |   |
| Regulatory compliance                                      | CE  |   |
| Electro-optical specifications                             |   |   |
| Image format [pixels]                                      | 640x512   |   |
| Pixel pitch [µm]   | 20  |   |
| Detector type  | InGaAs photodiode array with CTIA ROIC  |   |
| Sensor temperature stabilization                           | TE-cooler   |   |
| Integration type   | Snapshot - Global Shutter   |   |
| Active area and diagonal [mm]                              | 12.8 x 10.24 (diagonal 16.4)  |   |
| Optical fill factor  | 100%  |   |
| Spectral range [nm]  | 900 - 1700  |   |
| Quantum efficiency   | ~80% (typical peak value)   |   |
| Gain modes   | High Gain (HG) & High Dynamic Range mode (HDR)                                |   |
| Full well capacities [electrons]                           | 65k (HG) & 550k (HDR)   |   |
| Read noise [electrons]                                     | 45 (HG) & 200 (HDR)   |   |
| Dark current [electrons/second]                            | < 100k  |   |
| Read out modes   | ITR/IWR   |   |
| Pixel operability  | >99.5%  |   |
| Preconfigured exposure time range [ms]                     | HDR ITR: 0.5 ms; HG ITR: 0.5 ms & 5 ms; HG IWR 0.5 ms & 3 ms                  |   |
| Max frame rate [Hz] (full frame)                           | 300   | 300   |
| Region of interest   | Yes   |   |
| Min region size [pixels]                                   | 8 x 8 (step size 4 pixels in X & 1 pixel in Y)                                |   |
| Max frame rate [Hz] (min region size)                      | >7 kHz  |   |
| Command and control  | CameraLink Base   | USB3 Vision   |
| Digital output format                                      | CameraLink Base (16 bit)  | USB3 Vision (16 bit)  |
| Trigger  | Connector: 2 trigger in & 2 trigger out - LVCMOS 3.3 V; CameraLink trigger in | Connector: 2 trigger in & 2 trigger out - LVCMOS 3.3 V; CameraLink trigger in |
| Product selector guide                                     |   |   |
| Part number  | XEN-000874  | XEN-000873  |



For more information on our products  
Please scan the QR code.

