



Quantum Design EUROPE D-6425

Quantum Design GmbH Im Tiefen See 58 D-64293 Darmstadt



Latest-generation design for ultra-low temperature applications



Model 372 features

- Patented noise rejection technology
- Highly versatile and reliable measurement input
- Ability to increase the number of measurement channels to a maximum of 16 with optional 3726 scanner
- Dedicated input for ultra-low temperature control
- Powerful impedance measurement capabilities such as quadrature measurements
- Multiple PID controllable outputs with up to 10 W of heater power available
- Latest generation front panel for ease of use
- 3-year standard warranty



Introduction

The Model 372 AC resistance bridge and temperature controller builds on the solid foundation provided by the original Lake Shore AC resistance bridge. The Model 372 provides the best possible temperature measurement and control capabilities for dilution refrigerators (DRs) that are intended to be operated below 100 mK. The Model 372 makes it easy to perform multiple tasks that were once very difficult to perform reliably at ultra-low temperatures:

- Temperature measurement
- Automatic or manual temperature control
- Device or sample impedance measurements

Targeted applications

Ultra-low temperature measurement

Making measurements below 100 mK is far from a trivial exercise, with even the smallest amounts of added energy leading to self-heating and unwanted temperature shifts. Every design decision made on the Model 372 aims to minimize the amount of energy needed to take measurements.

U.S. Patent #6,501,255, Dec., 2002, "Differential current source with active common mode reduction," Lake Shore Cryotronics, Inc.



Quantum <mark>Design</mark> EUROPE Quantum Design GmbH Im Tiefen See 58 D-64293 Darmstadt



Noise rejection

Externally generated electronic noise can be a major cause of self-heating if it is allowed to couple into the device under test. Thankfully, multiple noise-rejection strategies have been implemented to reduce this effect substantially:

- Our patented* balanced noise-rejecting current source ensures that external signals have no path to ground through the measurement circuit, effectively making the Model 372 unaltered by these noise sources.
- The measurement signal cables use a driven guard that reduces parasitic capacitance in the cables that connect a scanner to the Model 372. This helps to further balance the measurement network and bolster the integrity of the noise rejection circuitry.
- All measurement circuitry is isolated from other instrument components, limiting the impact of any small electrical disturbances.
- The AC frequency options used for the measurement signal are selected to be naturally resilient to line voltage frequencies (50 and 60 Hz).

AC measurement signals

By using alternating current (AC) measurement in tandem with a specially designed internal lock-in amplifier, the Model 372 is able to extract very small measurement signals from background noise. This allows for much lower excitation levels to be used when compared to traditional direct current (DC) systems, minimizing the amount of energy that is dissipated into the device under test.

These AC excitation levels can be set to as low as 10 pA, while still maintaining accuracy of better than 1% over quite a wide range of resistances. This enables impedance and temperature measurements to be made while adding power levels so small that they are measured in the attowatt range (10⁻¹⁸ W). These features are vital in allowing accurate measurement to be made while minimizing the negative effects of self-heating.

Low noise signal recovery

Due to the very low excitation level used for measurement, the resulting voltage levels must first be boosted to allow those signals to be measured. The internal lock-in amplifier in the Model 372 has been specifically designed to minimize the amount of noise added to the signal. This results in an input noise figure that is less than 10 nV/Hz, thereby increasing the resolution of measurements and limiting the amount of post-measurement filtering that needs to be applied.

Model 372 rear panel



- 1 Scanner control input (DA-15)
- 2 Sensor voltage/current input (6-pin DIN)
- 3 Secondary control input (6-pin DIN)
- 4 Monitor output (BNC)

- 5 Reference output (BNC)
- 6 Sample heater output, warm-up heater output, and still
- heater output (terminal block)
 - 7 Relay 1 and 2 (terminal block)
- 8 Ethernet interface (RJ-45)
- 9 USB interface (USB Type A) 10 IEEE-488 2 interface
- 11 Line power/fuse assembly



Quantum <mark>Design</mark> EUROPE Quantum Design GmbH Im Tiefen See 58 D-64293 Darmstadt



Temperature measurement

Extremely accurate and reliable ultralow temperature measurements can be achieved by combining the Model 372 with a negative temperature coefficient (NTC) resistive temperature device (RTD), such as the Lake Shore Cernox[™], Rox[™] or germanium temperature sensors. Multiple calibration curves can easily be uploaded to the Model 372, allowing highly accurate conversion of sensor resistance to equivalent temperature using cubic spline interpolation (an improved interpolation technique compared to older instruments).



Cubic spline vs. linear interpolation

User-generated calibration curves can also be created and loaded into the Model 372, allowing great flexibility in the type of resistive sensors that are used. A maximum of 39 calibration curves can be stored on the instrument, and when used with a 3726 scanner, up to 17 sensors can be connected simultaneously, each with their own curve.

Measure a wide range of resistive devices

With up to 22 different current (I) excitation levels available, the Model 372 is able to perform accurate impedance measurements from several microohms ($10^{-6} \Omega$) to many megohms ($10^{6} \Omega$), all while keeping power dissipation levels to an absolute minimum.

The addition of full quadrature measurements means that both the resistive and reactive components of an impedance can now be measured. This enables much better characterization of the device under test by allowing capacitive or inductive components to be measured.

Expandability

For situations where temperature measurements must be taken at multiple locations, the 3726 scanner and preamp can be paired with the Model 372 to provide up to 16 connections for 4-wire resistance measurements. The Model 372 can switch measurement to any one of these connections as required, removing the need to physically switch cables on the instrument to look at different sensors. The measurement signal is also boosted by a pre-amp circuit in the 3726, preserving the signalto-noise ratio between the sensor and measurement circuitry of the Model 372. This allows connection cables of up to 10 m to be used between the Model 372 and the 3726.



The new 3726 scanner option

In cases where measurements are required at multiple locations simultaneously within an experiment space, additional Model 372 units may be used together. Five different AC excitation frequencies are available for this purpose, ensuring that up to five simultaneous measurements can be performed without the risk of co-channel interference.





Quantum Design

Quantum Design GmbH Im Tiefen See 58 D-64293 Darmstadt



Dilution Refrigerator Temperature Control

Making accurate measurements at ultra-low temperatures is no easy feat, especially when working in the ranges seen by modern dilution refrigerators. The Model 372 has many features specifically developed for dilution refrigerator applications.

Dedicated temperature control input

Taking measurements at ultra-low temperatures deserves uninterrupted attention from measurement devices. The Model 372 uses a dedicated temperature control input that is designed specifically for connection to a negative temperature coefficient resistive sensor. This input is designed to continuously monitor the temperature of the dilution refrigerator sample holder, while the measurement input scans through the multiple other temperature sensors placed throughout the dilution refrigerator.



The dedicated control input ensures uninterrupted dilution refrigerator temperature control

OUTPUTS

Multiple heater options

Three separate heater outputs are available on the Model 372:

- Sample heater-for fine control of the sample stage at ultra-low temperatures with up to 1 W
- of power available. Warm-up heater-supplying up to 10 W of power and featuring a warm-up
- mode specifically for the purpose of bringing the system temperature up to allow work to be performed on the sample stage.
- Still heater—an additional 1 W heater is available for the purpose of controlling the temperature of a dilution refrigerator's still. Alternatively, this output can provide an analog out signal to other devices if required.

A Model 372 and 3726 used to control a dilution refrigerator



The sample and warm-up heaters have many powerful control options, including PID control that allows both the setting of fixed temperature setpoints as well as ramp rates.

Stable temperature control

When operating at ultra-low temperatures, even small amounts of added energy can cause unwanted spikes in system temperature. The Model 372 heater outputs implement several protection mechanisms to reduce or eliminate this potential:

- The circuitry for the sample and still heaters are electrically isolated from other instrument sections
- Multiple power range settings allow extremely fine or coarse power transitions, depending on the need
- Heater outputs are shunted during power up and power range changes, eliminating the potential for unwanted power surges
- Terminal connections allow twisted pair cabling to be easily used for heater wiring; additional shielding of these wires can also be added to further reduce the potential of injecting noise into a system via the heater cabling

Thermal response characteristics of a

Temperature zone control

dilution refrigerator system can change quite dramatically over the useful range of operation, particularly down towards the lower temperature limit of a system, where cooling power is reduced. To accommodate these system variations, different PID values can be set for different temperature ranges ("zones"). This allows for more aggressive transition settings to be used at higher temperatures where system response is faster, and less reactive settings at low temperatures when temperature overshoots result in long recovery times.

Heater fail-safes

The Model 372 has several features that will protect your system and experiment from accidental deviations in planned temperature settings:

- Temperature thresholds can be set for all heater outputs, meaning the heaters will automatically shut down if it is detected that the system is being overheated.
- An easy-to-hit "ALL OFF" button is provided that shuts all heaters down instantly. This eliminates the terrible experience of having to hurriedly search through menu options while your experiment continues to heat.





Quantum <mark>Design</mark> EUROPE

Quantum Design GmbH Im Tiefen See 58 D-64293 Darmstadt



Low-Power Impedance Characterizationthe 3708 Scanner



Many material characterization experiments require measurements to be performed at cryogenic temperatures. This can be because the material behavior changes in interesting ways at these temperatures, or because background thermal noise must be minimized for useful measurement data to be extracted. The standard inputs of the Model 372 accurately measure higher-impedance devices such as temperature sensors, but begin to lose resolution and accuracy when extremely low impedances are encountered such as in Hall effect or superconducting material measurements. However, by adding a 3708 preamp and scanner to the Model 372, these materials can be characterized with the same accuracy and stability as when measuring higher-impedance devices.

To accomplish this, the 3708 produces higher levels of DC bias current than both the Model 372 and the 3726 scanner and preamp. This means the 3708 would cause self-heating in a temperature sensor used at ultra-low temperatures. The new dedicated control input resolves this issue by providing the ability to make highly reliable measurements of a temperature control sensor.

Lower input voltage noise

The limiting factor for making extremely low-impedance measurements directly with the Model 372 is the input voltage noise figure of 10 nV/√Hz. The preamp in the 3708 reduces this by a factor of 5 to an impressive 2 nV/√Hz. By reducing the amount of input noise, even smaller return signals can be recovered with excellent accuracy. When combined with the ability of the Model 372 to smooth measurement values with user-settable filters ranging from 1 to 200 s, the 3708 preamp and scanner provides the best solution to measuring lowimpedance devices at cryogenic temperatures.



Quantum <mark>Design</mark>

Quantum Design GmbH Im Tiefen See 58 D-64293 Darmstadt

Dr. Tobias Adler: ① +49 6151 8806-479, adler@qd-europe.com Find your local contact at www.qd-europe.com



FUROPE

Multiple simultaneous connections

The 3708 scanner and preamp allows up to eight simultaneous connections to be made, with the scanner feature enabling measurement to be switched between those connections. Unlike the 3726 scanner, all connections that are not actively being measured are left open, allowing the 3708 to be connected to Hall bar devices.

Overcoming cable length

With such small resultant voltages needing to be measured, it can be very helpful to have these signals amplified slightly as close as possible to the source of these signals. The compact size of the 3708 scanner and preamp allows it be mounted close to the device or sample being measured, thereby maintaining signal-to-noise ratio for the measurement signal between the sample and the Model 372 that will ultimately perform the measurements. Cable lengths of up to 10 m are supported by the 3708, allowing the Model 372 to be located away from the experiment area if needed.

Connectivity and Usability—Communication Options

Physical connectivity

Various methods for communicating with the Model 372 are made available:

- Ethernet: allows full control and reporting throughout an IP network.
- **USB:** provides direct serial communication by emulating a standard RS-232 connection.
- IEE-488.2: allows connection to GPIB systems.



Available functions

Multiple actions can be performed when connected to the Model 372 through one of its various remote access options:

- Send any command to the instrument that could be entered via the front panel
- Read and store measurement data that is generated by the instrument
- Live graphical viewing of data using the Lake Shore Cryotronics Chart Recorder software
- Load new calibration curves for use with new temperature sensors
- Upload new firmware if required

Backwards compatibility

The Model 372 is designed for trouble-free integration with existing equipment and software that has been built around the previous generation Model 370.

- Emulation mode on the Model 372 is designed to imitate all important communication functions of the Model 370. In most cases, programming that was previously written for the Model 370 can be used to interact with the Model 372.
- A convenient heater connector adapter (117-071) can also be purchased. This adapter replicates the BNC heater connections that were available on the Model 370, allowing connection swapping between the Model 372 and Model 370 without the need to rewire experiment cabling.



Quantum Design

Quantum Design GmbH Im Tiefen See 58 D-64293 Darmstadt



Dr. Tobias Adler: (1) +49 6151 8806-479, adler@qd-europe.com Find your local contact at www.qd-europe.com

Model 372 AC Resistance bridge and temperature controller

Sensor performance

Excitation ranges in sensor tables were selected to minimize sensor self-heating. Excitation power = actual current² × example resistance

Measurement resolution comes from electronic instrumentation and sensor thermal noises. Measurement resolution is given by: Resolution (Ω) = ((instrument noise at RT)²+(thermal noise of sensor at given temperature)²)^{0.5}

or Resolution (Ω) = ($N_i^2 + N_s^2$)^{0.5}

Where: N_i = instrument noise at room temperature

N_s = thermal noise of resistive sensor at given temperature

Electronic accuracy is influenced by the measurement range used and sensor resistance value. Electronic accuracy is given by: *Electronic accuracy* (Ω) = *Accuracy*(%)×*example resistance*+0.005% of resistance range Where: Accuracy (%) is given in the instrument performance table (pages 10–11) at the selected current and voltage range *Electronic accuracy* (*K*) = $\frac{Electronic accuracy(\Omega)}{(dR/dT)}$

Self-heating errors are measurement errors due to power dissipation in the sensor causing unwanted temperature rises. Self-heating error is given by:

Self heating error=thermal resistance×power

Thermal resistances specified are typical values resulting from minimal heat sinking.

Improved values can be achieved with permanent installation.

Calibration accuracies are based on Lake Shore sensor calibration uncertainty and repeatability values—see Appendices B, D & E of the Temperature Measurement and Control Catalog for more information.

Interpolation errors are due to the linear interpolation method used by the Model 372 to convert resistance values to temperatures when using a temperature sensor. These errors are not present when resistance is measured directly.

Overall accuracy is a combination of all listed sources of potential error and is given by: Overall accuracy = (measurement resolution² + electronic accuracy² + self heating errors² + calibration accuracy² + interpolation error²)^{0.5}

Lake Shore Rox™ RX-102B-CB with 0.02 to 40 K calibration

Values given are for measurement input. If the value is different for the control input, it is shown in blue.

	Sensor properties Excitation and instrumentation				ation	Instrument pe	erformance	Overall performance					
Temperature	Nominal resistance	Typical sensor sensitivity	Thermal resistance	Resistance range	Excitation voltage limit	Excitation current	Power	Measurement resolution	Electronic accuracy	Calibration accuracy	Self-heating errors	Interpolation error	Overall accuracy
20 mK	7.3 kΩ	-171 kΩ/K	17.2 K/nW	20 kΩ 632 kΩ	6.32 μV 200 μV	316 pA	730 aW	7.3 Ω (42.7 μK) 33.9 Ω (198 μK)	8.3 Ω (48.5 μK) 35.3 Ω (206 μK)	±2 mK	12.6 µK	±0.2 mK	2 mK
30 mK	6.0 kΩ	-100 kΩ/K	8.2 K/nW	6.32 kΩ 200 kΩ	6.32 μV 200 μV	1 nA	6 fW						
40 mK	5.2 kΩ	-62 kΩ/K	635.8 mK/nW	6.32 kΩ 63.2 kΩ	20 μV 200 μV	3.16 nA	52 fW	502 mΩ (δ.1 μκ) 1.5 Ω (24.2 μK)	2.9 Ω (46.8 μK) 4.7 Ω (75.8 μK)	±4 mK	33.1 µK	±0.2 mK	4 mK
50 mK	4.7 kΩ	-41 kΩ/K	415.1 mK/nW	6.32 kΩ 63.2 kΩ	20 μV 200 μV	3.16 nA	47 fW	502 mΩ (12.2 μK) 1.5 Ω (36.6 μK)	2.7 Ω (65.9 μK) 4.6 Ω (112 μK)	±4 mK	19.5 µK	±0.2 mK	4 mK
100 mK	3.5 kΩ	-13 kΩ/K	33.2 mK/nW	6.32 kΩ 20 kΩ	63.2 μV 200 μV	10 nA	350 fW	48.6 mΩ (3.7 μK) 338 mΩ (26 μK)	2.1 Ω (162 μK)	±4 mK	11.6 µK	±0.2 mK	4 mK
300 mK	2.5 kΩ	-2.4 kΩ/K	2.8 mK/nW	6.32 kΩ	200 µV	31.6 nA	2.5 pW	50.2 mΩ (20.9 μK) 87 mΩ (36.3 μK)	1.1 Ω (458 μK)	±4 mK	7.0 µK	±0.2 mK	4 mK
1 K	1.9 kΩ	-351 Ω/K	609.6 µK/nW	6.32 kΩ	200 µV	31.6 nA	1.9 pW	50.2 mΩ (143 μK) 87 mΩ (248 μK)	0.9 Ω (2.6 mK)	±4 mK	1.2 µK	±0.2 mK	4.7 mK



Resolution (K) = $\frac{\text{Resolution}(\Omega)}{(dR/dT)}$

Lake Shore GR-50-AA with 0.05 to 6 K calibration

Values given are for measurement input. If the value is different for the control input, it is shown in blue.

	Sensor p	roperties		Excitat	tion and in	strumenta	ation	Instrument p	erformance		Overall	performanc	e
Temperature	Nominal resistance	Typical sensor sensitivity	Thermal resistance	Resistance range	Excitation voltage limit	Excitation current	Power	Measurement resolution	Electronic accuracy	Calibration accuracy	Self-heating errors	Interpolation error	Overall accuracy
50 mK	35 kΩ	-3.6 MΩ/K	200 mK/nW	63.2 kΩ 200 kΩ	63.2 μV 200 μV	1 nA	35 fW	3.4 Ω (944 nK) 7.3 Ω (2 μK)	20.7 Ω (5.8 μK) 27.5 Ω (7.6 μK)	±4 mK	7.0 µK	±0.2 mK	4 mK
100 mK	2317 Ω	-72 kΩ/K	20 mK/nW	6.32 kΩ 20 kΩ	63.2 μV 200 μV	10 nA	232 fW	48.5 mΩ (674 nK) 338 mΩ (4.7 μK)	1.5 Ω (20.8 μK) 1.7 Ω (23.6 μK)	±4 mK	4.6 µK	±0.2 mK	4 mK
300 mK	164 Ω	-964 Ω/K	4 mK/nW	632 Ω 2 kΩ	200 µV	316 nA 100 nA	16 pW 1.6 pW	3.6 mΩ (3.7 μK) 29 mΩ (30.1 μK)	81 mΩ (84 μK) 149 mΩ (155 μK)	±4 mK	66 µК 6.6 µК	±0.2 mK	4 mK
500 mK	73.8 Ω	-202.9 Ω/K	1.2 mK/nW	632 Ω 2 kΩ	200 µV	316 nA 100 nA	7.4 pW 738 fW	3.6 mΩ (17.7 μK) 29 mΩ (143 μK)	54 mΩ (266 μK) 122 mΩ (601 μK)	±4 mK	8.9 μK 886 nK	±0.2 mK	4 mK 4.1 mK
1 K	34 Ω	-31 Ω/K	100 µK/nW	200 Ω 2 kΩ	200 µV	1 μA 100 nA	34 pW 340 fW	1.2 mΩ (38.7 μK) 29 mΩ (935 μK)	20 mΩ (645 μK) 110 mΩ (3.5 mK)	±4 mK	3.4 µК 34 nK	±0.2 mK	4.1 mK 5.4 mK
1.4 K	24.7 Ω	-13.15 Ω/K	75 μK/nW	200 Ω 2 kΩ	200 µV	1 μA 100 nA	25 pW 247 fW	1.2 mΩ (91.3 μK) 29 mΩ (2.2 mK)	17 mΩ (1.3 mK) 107 mΩ (8.1 mK)	±5 mK	1.9 µК 19 nK	±0.2 mK	5.2 mK 9.8 mK
4.2 K	13.7 Ω	-1.036 Ω/K	25 μK/nW	20 Ω 2 kΩ	200 µV	10 µА 100 nA	1.4 nW 137 fW	120 μΩ (116 μK) 29 mΩ (28 mK)	5.1 mΩ (4.9 mK) 104 mΩ (100 mK)	±5 mK	3.5 µК 3.4 nK	±0.2 mK	7 mK 104 mK

Lake Shore CX-1010-SD with 0.1 to 325 K calibration

Values given are for measurement input. If the value is different for the control input, it is shown in blue.

	Sensor properties			Excitation and instrumentation			Instrument performance		Overall performance				
Temperature	Nominal resistance	Typical sensor sensitivity	Thermal resistance	Resistance range	Excitation voltage limit	Excitation current	Power	Measurement resolution	Electronic accuracy	Calibration accuracy	Self-heating errors	Interpolation error	Overall accuracy
100 mK	21.389 kΩ	-558 kΩ/K	1.4 K/nW	63.2 kΩ 200 kΩ	63.2 μV 200 μV	1 nA	21 fW	3.4 Ω (6.1 μK) 7.4 Ω (13.3 μK)	13.9 Ω (24.9 μK) 20.7 Ω (37.1 μK)	±4 mK	30 µK	±0.2 mK	4 mK
300 mK	2.3224 kΩ	-10.8 kΩ/K	26.8 mK/nW	6.32 kΩ	200 µV	31.6 nA	2.3 pW	50.2 mΩ (4.6 μK) 87.0 mΩ (8.1 μK)	1.0 Ω (92.6 μK) 1.0 Ω (93.8 μK)	±4 mK	62 µK	±0.2 mK	4 mK
500 mK	1.2482 kΩ	-2.7 kΩ/K	4.3 mK/nW	2 kΩ	200 µV	100 nA	12.5 pW	14.5 mΩ (5.4 μK) 29.2 mΩ (10.8 μK)	475 mΩ (176 μK) 474 mΩ (176 μK)	±4 mK	54 µK	±0.2 mK	4 mK
4.2 K	277.32 Ω	-32.2 Ω/K	2 µK/nW	632 Ω 2 kΩ	6.32 mV 200 μV	10 µA 100 nA	28 nW 2.8 pW	1.3 mΩ (40.4 μK) 29.2 mΩ (907 μK)	115 mΩ (3.6 mK) 183 mΩ (5.7 mK)	±4 mK	56 μK 5.6 nK	±0.2 mK	5.4 mK 7 mK
300 K	30.392 Ω	-65.4 mΩ/K	426 fK/nW	63.2 Ω 2 kΩ	6.32 mV 200 μV	100 µА 100 nA	304 nW 304 fW	130 μΩ (2.0 mK) 29.2 mΩ (446 mK)	12.3 mΩ (188 mK) 109 mΩ (1.7 K)	±78 mK	130 pK 129 aK	±0.2 mK	203 mK 1.7 K



Quantum Design Ir

Quantum Design GmbH Im Tiefen See 58 D-64293 Darmstadt



372/3726 performance specification table

The values below apply to the measurement input. The control input operates over a reduced range indicated by the black-bordered cells. These cells contain bracketed numbers to indicate the resolution that applies to the control input.

							Voltage	e range					
		632 mV	200 mV	63.2 mV	20 mV	6.32 mV	2 mV	632 µV	200 µV	63.2 μV	20 µV	6.32 μV	2 µV
;	31.6 mA	20 Ω 20 μΩ 10 mW	6.32 Ω 6.3 μΩ 3.2 mW	2Ω 2μΩ 1 mW	632 mΩ 1.3 μΩ 320 μW	200 mΩ 400 nΩ 100 μW	63.2 mΩ 95 nΩ 32 μW	20 mΩ 36 nΩ 10 μW	6.32 mΩ 35 nΩ 3.2 μW	2 mΩ 40 nΩ 1 μW	* * *	* * *	* *
	10 mA	63.2 Ω 63 μΩ 3.2 mW	20 Ω 20 μΩ 1 mW	6.32 Ω 6.3 μΩ 320 μW	2 Ω 4 μΩ 100 μW	632 mΩ 1.3 μΩ 32 μW	200 mΩ 300 nΩ 10 μW	63.2 mΩ 120 nΩ 3.2 μW	20 mΩ 120 nΩ 1 μW	6.32 mΩ 130 nΩ 320 nW	2 mΩ 120 nΩ 100 nW	* *	* *
;	3.16 mA	200 Ω 200 μΩ 1 mW	63.2 Ω 63 μΩ 320 μW	20 Ω 20 μΩ 100 μW	6.32 Ω 13 μΩ 32 μW	2 Ω 4 μΩ 10 μW	632 mΩ 950 nΩ 3.2 μW	200 mΩ 390 nΩ 1 μW	63.2 mΩ 370 nΩ 320 nW	20 mΩ 400 nΩ 100 nW	6.32 mΩ 380 nΩ 32 nW	2 mΩ 400 nΩ 10 nW	* *
	1 mA	632 Ω 630 μΩ 3.2E-04	200 Ω 200 μΩ 100 μW	63.2 Ω 63 μΩ 32 μW	20 Ω 40 μΩ 10 μW	6.32 Ω 13 μΩ 3.2 μW	2 Ω 3 μΩ 1 μW	632 mΩ 1 μΩ 320 nW	200 mΩ 1 μΩ 100 nW	63.2 mΩ 1.3 μΩ 32 nW	20 mΩ 1.2 μΩ 10 nW	6.32 mΩ 1.3 μΩ 3.2 nW	2 mΩ 1 μΩ 1 nW
	316 µA	2 kΩ 2 mΩ 100 μW	632 Ω 630 μΩ 32 μW	200 Ω 200 μΩ 10 μW	63.2 Ω 130 μΩ 3.2 μW	20 Ω 40 μΩ 1 μW	6.32 Ω 9.5 μΩ 320 nW	2 Ω 3.8 μΩ 100 nW	632 mΩ 3.7 μΩ 32 nW	200 mΩ 4 μΩ 10 nW	63.2 mΩ 3.8 μΩ 3.2 nW	20 mΩ 4 μΩ 1 nW	6.32 mΩ 3.7 μΩ 320 pW
	100 µA	6.32 kΩ 6.3 mΩ 32 μW	2 kΩ 2 mΩ 10 μW	632 Ω 630 μΩ 3.2 μW	200 Ω 400 μΩ 1 μW	63.2 Ω 130 μΩ 320 nW	20 Ω 30 μΩ 100 nW	6.32 Ω 12 μΩ 32 nW	2 Ω 12 μΩ 10 nW	632 mΩ 13 μΩ 3.2 nW	200 mΩ 12 μΩ 1 nW	63.2 mΩ 13 μΩ 320 pW	20 mΩ 12 μΩ 100 pW
	31.6 µA	20 kΩ 20 mΩ 10 μW	6.32 kΩ 6.3 mΩ 3.2 μW	2 kΩ 2 mΩ 1 μW	632 Ω 1.3 mΩ 320 nW	200 Ω 400 μΩ 100 nW	63.2 Ω 95 μΩ 32 nW	20 Ω 37 μΩ 10 nW	6.32 Ω 37 μΩ 3.2 nW	2 Ω 40 μΩ 1 nW	632 mΩ 38 μΩ 320 pW	200 mΩ 40 μΩ 100 pW	63.2 mΩ 37 μΩ 32 pW
	10 µA	63.2 kΩ 63 mΩ 3.2 μW	20 kΩ 20 mΩ 1 μW	6.32 kΩ 6.3 mΩ 320 nW	2 kΩ 4 mΩ 100 nW	632 Ω 1.3 mΩ 32 nW	200 Ω 300 μΩ 10 nW	63.2 Ω 120 μΩ 3.2 nW	20 Ω 120 μΩ 1 nW	6.32 Ω 130 μΩ 320 pW	2 Ω 120 μΩ 100 pW	632 mΩ 130 μΩ 32 pW	200 mΩ 120 μΩ 10 pW
	3.16 µA	200 kΩ 200 mΩ 1 μW	63.2 kΩ 63 mΩ 320 nW	20 kΩ 20 mΩ 100 nW	6.32 kΩ 13 mΩ 32 nW	2 kΩ 4 mΩ 10 nW	632 Ω 950 μΩ 3.2 nW	200 Ω 370 μΩ 1 nW	63.2 Ω 370 μΩ 320 pW	20 Ω 400 μΩ 100 pW	6.32 Ω 380 μΩ 32 pW	2 Ω 400 μΩ 10 pW	632 mΩ 370 μΩ 3.2 pW
_	1 µA	632 kΩ 630 mΩ 320 nW	200 kΩ 200 mΩ 100 nW	63.2 kΩ 63 mΩ 32 nW	20 kΩ 40 mΩ 10 nW	6.32 kΩ 13 mΩ 3.2 nW	2 kΩ 3 mΩ 1 nW	632 Ω 1.2 mΩ 320 pW	200 Ω 1.2 mΩ 100 pW	63.2 Ω 1.3 mΩ 32 pW	20 Ω 1.2 mΩ 10 pW	6.32 Ω 1.3 mΩ 3.2 pW	2Ω 1.2 mΩ 1 pW
excitation	316 nA	2 MΩ 2 Ω 100 nW	632 kΩ 630 mΩ 32 nW	200 kΩ 200 mΩ 10 nW	63.2 kΩ 130 mΩ 3.2 nW	20 kΩ 40 mΩ 1 nW	6.32 kΩ 13 mΩ 320 pW	2 kΩ 4 mΩ 100 pW	632 Ω 3.8 mΩ 32 pW	200 Ω 4 mΩ 10 pW	63.2 Ω 3.8 mΩ 3.2 pW	20 Ω 4 mΩ 1 pW	6.32 Ω 3.8 mΩ 320 fW
Current e	100 nA	6.32 MΩ 32 nW	2 MΩ 2 Ω 10 nW	632 kΩ 630 mΩ 3.2 nW	200 kΩ 400 mΩ 1 nW	63.2 kΩ 130 mΩ 320 pW	20 kΩ 30 mΩ 100 pW	6.32 kΩ 13 mΩ 32 pW	2 kΩ 16 [30] mΩ 10 pW	632 Ω 13 mΩ 3.2 pW	200 Ω 12 mΩ 1 pW	63.2 Ω 13 mΩ 320 fW	20 Ω 12 mΩ 100 fW
	31.6 nA	20 MΩ ** 10 nW	6.32 MΩ ** 3.2 nW	2 MΩ 2 Ω 1 nW	632 kΩ 1.3 Ω 320 pW	200 kΩ 300 mΩ 100 pW	63.2 kΩ 160 mΩ 32 pW	20 kΩ 100 mΩ 10 pW	6.32 kΩ 63 [95] mΩ 3.2 pW	2 kΩ 40 mΩ 1 pW	632 Ω 38 mΩ 320 fW	200 Ω 40 mΩ 100 fW	63.2 Ω 38 mΩ 32 fW
	10 nA	63.2 MΩ 3.2 nW	20 MΩ ** 1 nW	6.32 MΩ ** 320 pW	2 ΜΩ 3 Ω 100 pW	632 kΩ 1.6 Ω 32 pW	200 kΩ 600 mΩ 10 pW	63.2 kΩ 470 mΩ 3.2 pW	20 kΩ 300 [400] mΩ 1 pW	6.32 kΩ 130 mΩ 320 fW	2 kΩ 160 mΩ 100 fW	632 Ω 130 mΩ 32 fW	200 Ω 120 mΩ 10 fW
	3.16 nA	* *	63.2 MΩ 320 pW	20 MΩ ** 100 pW	6.32 MΩ ** 32 pW	2 MΩ 9 Ω 10 pW	632 kΩ 4.7 Ω 3.2 pW	200 kΩ 3 Ω 1 pW	63.2 kΩ 1.6 [1.9] Ω 320 fW	20 kΩ 1 Ω 100 fW	6.32 kΩ 630 mΩ 32 fW	2 kΩ 500 mΩ 10 fW	632 Ω 380 mΩ 3.2 fW
	1 nA	* * *	* * *	63.2 MΩ ** 32 pW	20 MΩ ** 10 pW	6.32 MΩ ** 3.2 pW	2 MΩ 30 Ω 1 pW	632 kΩ 16 Ω 320 fW	200 kΩ 6 [10] Ω 100 fW	63.2 kΩ 5.1 Ω 32 fW	20 kΩ 3 Ω 10 fW	6.32 kΩ 1.3 Ω 3.2 fW	2 kΩ 1.6 Ω 1 fW
	316 pA	* * *	* * *	* * *	63.2 MΩ ** 3.2 pW	20 MΩ ** 1 pW	6.32 MΩ ** 320 fW	2 MΩ 90 Ω 100 fW	632 kΩ 47 [51] Ω 32 fW	200 kΩ 30 Ω 10 fW	63.2 kΩ 16 Ω 3.2 fW	20 kΩ 10 Ω 1 fW	6.32 kΩ 6.3 Ω 320 aW
	100 pA	* * *	* 200 kΩ	* — resistance ran	* ge	63.2 MΩ ** 320 fW	20 MΩ ** 100 fW	6.32 MΩ ** 32 fW	2 MΩ 300 Ω 10 fW	632 kΩ 160 Ω 3.2 fW	200 kΩ 100 Ω 1 fW	63.2 kΩ 51 Ω 320 aW	20 kΩ 30 Ω 100 aW
	31.6 pA	* * *	100 Ω [150 Ω] - 1.0 fW	 measurement [control resolu power 	resolution ition]	* * *	63.2 MΩ ** 32 fW	20 MΩ ** 10 fW	6.32 MΩ ** 3.2 fW	2 MΩ 900 Ω 1 fW	632 kΩ 470 Ω 320 aW	200 kΩ 300 Ω 100 aW	63.2 kΩ 160 Ω 32 aW
	10 pA	* * *	Resistance rang resistance rang over range. Resolution: RM	n ge: Full scale le, nominal 20% //S noise with 19	Acc	* curacy	*	63.2 MΩ ** 3.2 fW	20 MΩ ** 1 fW	6.32 MΩ ** 320 aW	2 MΩ 3 kΩ 100 aW	632 kΩ 1.6 kΩ 32 aW	200 kΩ 1 kΩ 10 aW
	3.16 pA	* * *	filter settling tin 3 s analog time specified at ½ f	ne (approximate constant). Noisi full scale resista	e nce	$\pm 0.03\% + 0.00$ $\pm 0.05\% + 0.00$ $\pm 0.1\% + 0.010$	05% of range 08% of range	* * *	63.2 MΩ ** 320 aW	20 MΩ ** 100 aW	6.32 MΩ ** 32 aW	2 MΩ 9 kΩ 10 aW	632 kΩ 4.7 kΩ 3.2 aW
	1 pA	* * *	Power: Excitati one-half full sca Precision: Dom	ature. on power at ale resistance. hinated by		$\pm 0.3\% + 0.013$ $\pm 0.3\% + 0.05^{\circ}$ $\pm 0.5\% + 0.08^{\circ}$	% of range % of range	* * *	* * *	63.2 MΩ ** 32 aW	20 MΩ ** 10 aW	6.32 MΩ ** 3.2 aW	2 MΩ 30 kΩ 1 aW
			measurement t coefficient (±0. ±0.0002% of ra	emperature 0015% of readii ange)/°C	ng * /	±1.0% + 0.15 Range not availa	% of range able						

** Range available, not specified



Quantum DesignQuantum Design GmbHEUROPEIm Tiefen See 58D-64293 Darmstadt



372/3708 performance specification table

					Voltage rang	e		
	6.32 mV	2.0 mV	632 µV	200 µV	63.2 μV	20 µV	6.32 µV	2.0 µV
31.6 mA	200 mΩ 200 nΩ 100 μW	63.2 mΩ 63 nΩ 32 uW	20 mΩ 40 nΩ 10 μW	6.32 mΩ 13 nΩ 3.2 μW	2.0 mΩ 10 nΩ 1.0 μW	* * *	* * *	* * *
10 mA	632 mΩ 630 nΩ 32 uW	200 mΩ 200 nΩ 10 uW	63.2 mΩ 130 nΩ 3.2 μW	20 mΩ 40 nΩ 1.0 μW	6.32 mΩ 32 nΩ 320 nW	2.0 mΩ 32 nΩ 100 nW	* * *	* * *
3.16 mA	2.0 Ω 2.0 μΩ 10 μW	632 mΩ 630 nΩ 3.2 μW	200 mΩ 400 nΩ 1.0 μW	63.2 mΩ 130 nΩ 320 nW	20 mΩ 100 nΩ 100 nW	6.32 mΩ 100 nΩ 32 nW	2.0 mΩ 100 nΩ 10 nW	* * *
1 mA	6.32 Ω	2.0 Ω	632 mΩ	200 mΩ	63.2 mΩ	20 mΩ	6.32 mΩ	2.0 mΩ
	6.3 μΩ	2.0 μΩ	1.3 μΩ	400 nΩ	320 nΩ	320 nΩ	320 nΩ	320 nΩ
	3.2 μW	1.0 μW	320 nW	100 nW	32 nW	10 nW	3.2 nW	1.0 nW
316 µA	20 Ω	6.32 Ω	2.0 Ω	632 mΩ	200 mΩ	63.2 mΩ	20 mΩ	6.32 mΩ
	20 μΩ	6.3 μΩ	4.0 μΩ	1.3 μΩ	1.0 μΩ	1.0 μΩ	1.0 μΩ	1.0 μΩ
	1.0 μW	320 nW	100 nW	32 nW	10 nW	3.2 nW	1.0 nW	320 pW
100 µA	63.2 Ω	20 Ω	6.32 Ω	2.0 Ω	632 mΩ	200 mΩ	63.2 mΩ	20 mΩ
	63 μΩ	20 μΩ	13 μΩ	4.0 μΩ	3.2 μΩ	3.2 μΩ	3.2 mΩ	3.2 μΩ
	320 nW	100 nW	32 nW	10 nW	3.2 nW	1.0 nW	320 pW	100 pW
31.6 µA	200 Ω	63.2 Ω	20 Ω	6.32 Ω	2.0 Ω	632 mΩ	200 mΩ	63.2 mΩ
	200 μΩ	63 μΩ	40 μΩ	13 μΩ	10 μΩ	10 μΩ	10 μΩ	10 μΩ
	100 nW	32 nW	10 nW	3.2 nW	1.0 nW	320 pW	100 pW	32 pW
10 µA	632 Ω	200 Ω	63.2 Ω	20 Ω	6.32 Ω	2.0 Ω	632 mΩ	200 mΩ
	630 μΩ	200 μΩ	130 μΩ	40 μΩ	32 μΩ	32 μΩ	32 μΩ	32 μΩ
	32 nW	10 nW	3.2 nW	1.0 nW	320 pW	100 pW	32 pW	10 pW
3.16 µA	2.0 kΩ	632 Ω	200 Ω	63.2 Ω	20 Ω	6.32 Ω	2.0 Ω	632 mΩ
	2.0 mΩ	630 μΩ	400 μΩ	130 μΩ	100 μΩ	100 μΩ	100 μΩ	100 μΩ
	10 nW	3.2 nW	1.0 nW	320 pW	100 pW	32 pW	10 pW	3.2 pW
Aμ1 ation	6.32 kΩ 6.3 mΩ 3.2 nW	2.0 kΩ 2.0 mΩ 1.0 nW	632 Ω 1.3 mΩ 320 pW	200 Ω 400 μΩ 100 pW	63.2 Ω 320 μΩ 32 pW	20 Ω 320 μΩ 10 pW	6.32 Ω 320 μΩ 3.2 pW	2.0 Ω 320 μΩ 1.0 pW
316 nA	20 kΩ	6.32 kΩ	2.0 kΩ	632 Ω	200 Ω	63.2 Ω	20 Ω	6.32 Ω
	20 mΩ	6.3 mΩ	4.0 mΩ	1.3 mΩ	1.0 mΩ	1.0 mΩ	1.0 mΩ	1.0 mΩ
	1.0 nW	320 pW	100 pW	32 pW	10 pW	3.2 pW	1.0 pW	320 fW
100 nA	63.2 kΩ	20 kΩ	6.32 kΩ	2.0 kΩ	632 Ω	200 Ω	63.2 Ω	20 Ω
	63 mΩ	40 mΩ	13 mΩ	6.0 mΩ	3.2 mΩ	3.2 mΩ	3.2 mΩ	3.2 mΩ
	320 pW	100 pW	32 pW	10 pW	3.2 pW	1.0 pW	320 fW	100 fW
31.6 nA	200 kΩ	63.2 kΩ	20 kΩ	6.32 kΩ	2.0 kΩ	632 Ω	200 Ω	63.2 Ω
	400 mΩ	130 mΩ	60 mΩ	20 mΩ	20 mΩ	10 mΩ	10 mΩ	10 mΩ
	100 pW	32 pW	10 pW	3.2 pW	1.0 pW	320 fW	100 fW	32 fW
10 nA	632 kΩ	200 kΩ	63.2 kΩ	20 kΩ	6.32 kΩ	2.0 kΩ	632 Ω	200 Ω
	1.9 Ω	600 mΩ	200 mΩ	200 mΩ	63 mΩ	63 mΩ	32 Ω	32 mΩ
	32 pW	10 pW	3.2 pW	1.0 pW	320 fW	100 fW	32 fW	10 fW
3.16 nA	2.0 MΩ	632 kΩ	200 kΩ	63.2 kΩ	20 kΩ	6.32 kΩ	2.0 kΩ	632 Ω
	6.0 Ω	2.0 Ω	2.0 Ω	630 mΩ	600 mΩ	200 mΩ	200 mΩ	100 mΩ
	10 pW	3.2 pW	1.0 pW	320 fW	100 fW	32 fW	10 fW	3.2 fW
1 nA	6.32 MΩ	2.0 MΩ	632 kΩ	200 kΩ	63.2 kΩ	20 kΩ	6.32 kΩ	2.0 kΩ
	**	20 Ω	6.3 Ω	6.0 Ω	3.2 Ω	2.0 Ω	630 mΩ	1.0 Ω
	3.2 pW	1.0 pW	320 fW	100 fW	32 fW	10 fW	3.2 fW	1.0 fW
316 pA	* *	6.32 MΩ ** 320 fW	2.0 MΩ 60 Ω 100 fW	632 kΩ 19 Ω 32 fW	200 kΩ 20 Ω 10 fW	63.2 kΩ 6.3 Ω 3.2 fW	20 kΩ 3.0 Ω 1.0 fW	6.32 kΩ 3.2 Ω 320 aW
100 pA	* * *	* * *	6.32 MΩ ** 32 fW	2.0 MΩ 200 Ω 10 fW	632 kΩ 63 Ω 3.2 fW	200 kΩ 60 Ω 1.0 fW	63.2 kΩ 32 Ω 320 aW	20 kΩ 20 Ω 100 aW
31.6 pA	* * *	* * *	* * *	6.32 MΩ ** 3.2 fW	2.0 MΩ 600 Ω 1.0 fW	632 kΩ 190 Ω 320 aW	200 kΩ 200 Ω 100 aW	63.2 kΩ 63 Ω 32 aW
10 pA	* * *	* * *	* * *	* *	6.32 MΩ ** 320 aW	2.0 MΩ 2.0 kΩ 100 aW	632 kΩ 630 Ω 32 aW	200 kΩ 600 Ω 10 aW
3.16 pA	* * *	* * *	* * *	* * *	* * *	6.32 MΩ ** 32 aW	2.0 MΩ 6.0 kΩ 10 aW	632 kΩ 1.9 kΩ 3.2 aW

200 kΩ resistance range measurement resolution 100 Ω ----1.0 fW -----

Resistance range: Full scale resistance range, nominal 20% over

range. Resolution: RMS noise with 18 s filter settling time (approximates 3 s analog time constant). Noise specified at ½ full scale resistance at room temperature. Power: Excitation power at one-half full scale resistance. Precision: Dominated by measurement temperature coefficient (±0.0015% of reading ±0.0002% of range)/°C.

Accuracy

±0.03% + 0.005% of range ±0.05% + 0.008% of range ±0.1% + 0.015% of range ±0.3% + 0.05% of range ±0.5% + 0.08% of range ±1.0% + 0.15% of range * Range not available ** Range available, not specified

G

11

Quantum Design GmbH Im Tiefen See 58 D-64293 Darmstadt



Specifications

Measurement input

Input type	AC, four-lead differential, resistance
Number of inputs	1
Maximum channels	16 (with optional scanner)
Measurement units	Ω, K (with temperature curve)
Resistance ranges	22 ranges from 2 m Ω to 63.2 M Ω (excitation dependent)
Maximum update rate	10 rdg/s (single range and input)
Range change settling	3 s + filter settling
Channel change (scan) settling	3 s + filter settling
Resolution	Sensor and range dependent, refer to Measurement Input Specifications table
Accuracy	Sensor and range dependent refer to Measurement Input
, loour doy	Specifications table
Temperature coefficient	+0.0015%/°C of rdg
Maximum lead resistance	$100.0 \pm 10\%$ of resistance range per lead for current
Maximum load resistance	$<3.16 \text{ mA} \cdot 10.0 \pm 10\%$ of resistance range per lead for
	current >10 mA
Isolation	Isolated from chassis and heater grounds
Lead connections	V + V - I + I - V shield I shield individual quards
Scanner lead connections	V_+ V ₋ I ₊ I ₋ for each sensor shield common to all
Common mode rejection	Matched impedance voltage input and current output
	active CMR
Excitation	Sinusoidal AC current source
Excitation frequency	9.8 Hz, 11.6 Hz, 13.7 Hz (default), 18.2 Hz, or 16.2 Hz
Excitation currents	22 ranges from 1 pA to 31.6 mA RMS
Excitation accuracy	±2% of nominal
Minimum excitation power	10^{-18} W into a 100 k Ω (see Measurement Input Specifications table for other ranges)
Typical DC bias current	2 pA + 1% of excitation current (4.0×10^{-19} W into 100 k Ω)
Maximum DC bias current	$4 \text{ pA} + 1\%$ of excitation current $(1.6 \times 10^{-18} \text{ W into } 100 \text{ k}\Omega)$
Power up current protection	Current output shunted on power up
Voltage input ranges	12 ranges from 2 µV to 632 mV RMS
Voltage input over-range	20%
Voltage input impedance	>5 × 1013 Ω
Maximum input voltage noise	10 nV/_/Hz at 10 Hz
Range selection modes	Manual, voltage excitation, current excitation, autorange
Scanner modes	Manual or autoscan
Filter	1 s to 200 s settling time, 1% to 80% filter window
Additional software features	Min/Max reading capture, pause (3 s to 60 s) on range and/or
	channel change, scanner dwell time (1 s to 200 s)
Supported sensors	NTC resistive sensors including germanium. Cernox [™] . Rox [™] .
	PTC resistive sensors including rhodium-iron
Quadrature display	Real and Imaginary
Connectors	6-pin DIN (current out), 6-pin DIN (voltage in), and DB15
	(scanner control)
Supported scanners	Lake Shore 3726 and 3708

Control input

Input type
Number of inputs
Measurement units
Resistance ranges
Maximum update rate
Range change settling
Resolution
Accuracy

Temperature coefficient Maximum lead resistance Isolation Lead connections Common mode rejection Excitation Excitation frequency

 $\Omega,\,K$ (with temperature curve) 6 ranges from 2 k Ω to 632 k Ω (excitation dependent) 10 rdg/s (single range) 3 s + filter settling Sensor and range dependent, refer to Control Input Specifications table Sensor and range dependent, refer to Control Input Specifications table ±0.0015%/°C of reading $100 \Omega + 10\%$ of resistance range per lead

AC, four-lead differential, resistance

Isolated from chassis, common to measurement input V+, V-, I+, I-, shield Matched impedance voltage input and current output Sinusoidal AC current source

9.8 Hz, 11.6 Hz, 13.7 Hz, 16.2 Hz (default), or 18.2 Hz

Excitation currents	6 ranges from 316 pA to 100 nA RMS
Excitation accuracy	±8% of nominal for 316 pA and 1 nA ranges;
	±2% of nominal for the other ranges
Power up current protection	Current output shunted on power up
Voltage input range	200 µV
Voltage input over-range	20%
Maximum input voltage noise	20 nV/√Hz at 10 Hz
Range selection modes	Manual, standard autorange, and Rox [™] RX-102B-CB optimized autorange
Filter	1 s to 200 s settling time, 1% to 80% filter window
Additional software features	Min/Max reading capture
Supported sensors	NTC resistive sensors (optimized for Rox [™] RX-102B-CB sensor)
Minimum temperature	Down to 10 mK using a Rox™ RX-102B-CB sensor in a well designed system
Connector	6-pin DIN

Temperature conversion

Sensor temperature coefficient	Negative or positive
User curves	Up to 39 CalCurves™ or user curves (200-point)
Curve entry	Via front panel or computer interface
Curve format	Ω/Κ, Log Ω/Κ
Curve interpolation	Cubic spline, linear

Sample heater output

Туре	Variable DC current source
Control modes	Closed loop PID, PID zones, open loop
Setpoint units	Ω, K (with temperature curve)
D/A resolution	16-bit
Ranges	100 mA, 31.6 mA, 10 mA, 3.16 mA, 1 mA, 316 μA, 100 μA, 31.6 μA
Output compliance voltage (min)	±10 V
Maximum power of output ranges	1 W, 100 mW, 10 mW, 1 mW, 100 $\mu\text{W},$ 10 $\mu\text{W},$ 1 $\mu\text{W},$ 0.1 μW
Resistance range	1 Ω to 2 k Ω , 100 Ω for maximum power
Heater offset (at 0%)	±0.02% of range
Heater gain accuracy	±1% of setting
Heater noise	<0.005% of range
Isolation	Isolated from chassis ground, measurement and control inputs; shared ground with analog/still output
Heater connector	Detachable terminal block
Safety limits	Curve temperature, power up heater off, shunted with a relay on power up, selectable heater range limit, short-circuit protection, compliance voltage limit detection, input temperature limit
Additional software features	Heater power display based on user entered resistance

Warm-up heater output

Туре	Variable DC current source	
Control modes	Closed loop PID, PID zones,	open loop, warm-up mode
Setpoint units	Ω, K (with temperature curv	e)
D/A resolution	16-bit	
	25 Ω setting	50 Ω setting
Maximum power	10 W	10 W
Maximum current	0.63 A	0.45 A
Voltage compliance (min)	+15.8 V	+22.4 V
Heater load for maximum power	25 Ω	50 Ω
Resistance range	10 Ω to 100 Ω	
Isolation	Chassis ground reference	
Heater connector	Detachable terminal block	
Safety limits	Curve temperature, power u with a relay on power up, sl compliance voltage limit, re when off input temperature	up heater off, shunted nort-circuit protection, lay disconnects output



Quantum <mark>Design</mark> EUROPE

Quantum Design GmbH Im Tiefen See 58 D-64293 Darmstadt



Analog/still output

Type Control modes Isolation

Output voltage range Maximum current Maximum power Minimum load resistance Accuracy Noise (resolution) Monitor output settings Scale Data source Settings Connector \pm 10 V 100 mA 1 W into 100 Ω 100 Ω (short-circuit protected) \pm 2.5 mV <0.003% of range User selected Temperature or sensor units Input, source, top of scale, and bottom of scale Detachable terminal block

Variable DC voltage source

Open loop, still heater, monitor output

inputs; shared ground with sample heater

Isolated from chassis ground, measurement and control

Heater control Number of control loops Update rate Tuning PID control settings Proportional (gain) Integral (reset) Derivative (rate) Manual output Zone control

0.001 to 1,000
 0 to 10,000 s
 0 to 2,500 s
 0 to 100% with 0.01% setting resolution
 10 temperature zones with P, I, D, manual heater out, heater range, setpoint, relays, and analog output (still)
 0.001 K/min to 100 K/min
 Control with scanned channel (reduced stability)
 Below 10 µK p-p at 50 mK (system dependent)

2 (sample heater, warm-up heater)

10/s Manual PID. zone

Warm-up heater mode settings

Warm-up percentage0 to 100% with 1% resolutionWarm-up modeContinuous control or auto-off

Front panel

Setpoint ramping

Scanner support

Control stability

Display 8-line by 40-character (256 \times 64 pixel) graphic VF display module Number of reading displays 1 to 8 Display units mK, K, mΩ, Ω, kΩ, MΩ Reading source Resistance, temperature, max, min Display update rate 2 rda/s Other displays Input name, channel number, resistance range, excitation voltage, excitation current, excitation power, control setpoint, PID, heater range, heater output, and quadrature reading Same as display resolution (sensor-dependent) Setpoint setting resolution Numeric display in percent of full scale for power or current Heater output display **Display annunciators** Control input and alarm Autorange, excitation mode, autoscan, control outputs, LED annunciators remote, Ethernet status, alarm, still output Keypad 34-key silicone elastomer keypad Front panel features Front panel curve entry, and keypad lock-out

Interface

IEEE-488.2 Capabilities SH1, AH1, T5, L4, SR1, RL1, PP0, DC1, DT0, C0, E1 To 10 rdg/s on each input LabVIEW[™] driver (see www.lakeshore.com) Update rate Software support LISR Function Emulates a standard RS-232 serial port Baud rate 57,600 Connector B-type USB connector Update rate To10 rdg/s on each input LabVIEW™ driver (see www.lakeshore.com) Software support Fthernet Function TCP/IP, web interface, curve handler, configuration backup, chart recorder R.I-45 Connector To 10 rdg/s on each input LabVIEW™ driver (see www.lakeshore.com) Update rate Software support Special interface feature Model 370 command emulation mode Available baud rates 300, 1,200, 9,600, 57,600 Alarms Number 34, high and low for each measurement channel and the control input Data source Temperature or sensor units Settings Source, high setpoint, low setpoint, deadband, latching or non-latching, audible on/off, visible on/off Display annunciator, beeper, and relays Actuators Relavs Number 2 Normally open (NO), normally closed (NC), and common (C) Contacts Contact rating 30 VDC at 2 A Operation Activate relays on high, low, or both alarms for any measurement channel or control input, manual mode, or zone control mode Connector Detachable terminal block monitor output Diagnostic monitor output Operation User selects one of several analog voltage diagnostic points (must remain isolated) Available signals 1. AC voltage driving positive/negative side of current source programming resistor 2. AC voltage present on the positive/negative side of the differential input amplifier 3. AC voltage present on the output of the differential input amplifier 4. AC voltage into the measurement channel or control input AD converter Connector BNC Reference output Signal type Phase-sensitive detector reference (must remain isolated) Amplitude 0 to +5 V nominal Waveform Square wave Connector BNC General Ambient temperature 15 °C to 35 °C at rated accuracy; 5 °C to 40 °C at reduced accuracy 100, 120, 220, 240 VAC, ±10%, 50 or 60 Hz, 90 VA Power requirement 435 mm W \times 89 mm H \times 368 mm D (17 in \times 3.5 in \times Size 14.5 in), full rack 6.8 kg (15 lb) Weight CE mark, RoHS Approval

135 mm W \times 66 mm H \times 157 mm D (plus connector

clearance of 125 mm)



Quantum Design

Quantum Design GmbH Im Tiefen See 58 D-64293 Darmstadt Dr. Tobias Adler: ① +49 6151 8806-479, adler@qd-europe.com Find your local contact at www.qd-europe.com

Scanner size



The Rox™ RX-102B-CB

The RX-102B-CB (1000 Ω at room temperature) is useful down to 10 mK (calibrations available down to 20 mK) and monotonic from 10 mK to 300 K. The unique package design maximizes thermal connection and minimizes heat capacity at ultra low temperatures. The RX-102B-CB is not interchangeable to a standard curve and not recommended for use in magnetic fields.





General tolerance of ± 0.127 mm (0.005 in) on X.XXX and ± 0.254 mm (0.01 in) on X.XX unless otherwise noted Mount using a #6 or M3 screw

Meet the Entire Family of Lake Shore Temperature Instruments





EUROPE

Quantum Design GmbH Quantum Design Im Tiefen See 58 D-64293 Darmstadt



Ordering information

Part number	Description
372N	AC resistance bridge and temperature controller with no connection cable
372U	AC resistance bridge with 3708 scanner and standard 3 m (10 ft) connection cable
372U-6	AC resistance bridge with 3708 scanner and 6 m (20 ft) connection cable
372U-10	AC resistance bridge with 3708 scanner and 10 m (33 ft) connection cable
372S	AC resistance bridge with 3726 scanner and standard 3 m (10 ft) connection cable
372S-6	AC resistance bridge with 3726 scanner and 6 m (20 ft) connection cable
372S-10	AC resistance bridge with 3726 scanner and 10 m (33 ft) connection cable

Please indicate your power/cord configuration:

- 1 100 V-U.S. cord (NEMA 5-15)
- 2 120 V-U.S. cord (NEMA 5-15)
- 3 220 V—Euro cord (CEE 7/7)
- 4 240 V—Euro cord (CEE 7/7)
- 5 240 V—U.K. cord (BS 1363)
- 6 240 V—Swiss cord (SEV 1011) 7 220 V—China cord (GB 1002)

Scanners

3708	Ultra-low resistance 8-channel scanner with standard 3 m (10 ft) connection cable—
	includes one scanner cable and bracket kit (117-035)
3708-0	Ultra-low resistance 8-channel scanner with no connection cable
3708-6	Ultra-low resistance 8-channel scanner with 6 m (20 ft) connection cable
3708-10	Ultra-low resistance 8-channel scanner with 10 m (33 ft) connection cable
3726	16-channel scanner with standard 3 m (10 ft) connection cable (Model 372 only)
3726-0	16-channel scanner with no connection cable (Model 372 only)
3726-6	16-channel scanner with 6 m (20 ft) connection cable (Model 372 only)
3726-10	16-channel scanner with 6 m (20 ft) connection cable (Model 372 only)

Accessories/options

1 m (3.3 ft) IEEE-488 (GPIB) computer interface cable assembly—includes extender
required for simultaneous use of IEEE cable and relay terminal block
Instrument recalibration with certificate
Instrument recalibration with certificate and data
Kit for mounting one full rack instrument in a 482.6 mm (19 in) rack mount cabinet
Sensor input mating connector (6-pin DIN plug)
3 m (10 ft) AC resistance bridge cable
6 m (20 ft) AC resistance bridge cable
10 m (33 ft) AC resistance bridge cable
Model 372 heater adapter cable
Model 372 user manual

All specifications are subject to change without notice



Quantum <mark>Design</mark> EUROPE

Quantum Design GmbH Im Tiefen See 58 D-64293 Darmstadt



Model 372 AC

Resistance bridge and temperature controller

Lake Shore Cryogenic Sensors, Instruments, and Accessories

Temperature Sensors

AC Resistance Bridge

Temperature Controllers

Temperature Monitors

Temperature Transmitters

Programmable DC Current Source

Superconducting Magnet Power Supply

Cryogenic Accessories

Reference Materials

©2017 Lake Shore Cryotronics, Inc. All rights reserved.

The technical information contained herein is subject to change at any time. 060717

About Lake Shore Cryotronics, Inc.

Supporting advanced research since 1968, Lake Shore is a leading innovator in measurement and control solutions for materials characterization under extreme temperature and magnetic field conditions. High-performance product solutions from Lake Shore include cryogenic temperature sensors and instrumentation, magnetic test and measurement systems, probe stations, and precision materials characterizations systems that explore the electronic and magnetic properties of next-generation materials. Lake Shore serves an international base of research customers at leading university, government, aerospace, and commercial research institutions and is supported by a global network of sales and service facilities.



Quantum Design

Quantum Design GmbH Im Tiefen See 58 D-64293 Darmstadt

