



THE MOST ADVANCED
**BENCHTOP
MICRO XRF
ON THE MARKET**



**X
M**

www.ixrf.com

Phone: 512.386.6100 | info@ixrf.com

IXRF
SYSTEMS



Product Features

- Smallest spot $\geq 5\mu\text{m}$
- Hottest Tube
- Largest Chamber
- Largest detector 150mm²
- Light element detection from C (6) to U (92)
- Up to 4 detectors
- Largest, highest resolution maps
- Sub-micron stage accuracy
- Runs in air, under vacuum, with He
- Most advanced software

ATLAS X TECHNICAL SPECIFICATIONS

Sample Types	Solids, Liquids, Particles, Powders
Sample Chamber Size	37x26x14in (950x650x365mm)
Measurement Media	Air, Vacuum, He
Excitation Source	Primary 50W / 50kV / 1mA Secondary 4W-12W / 40kV-60kV / 0.4mA-1mA
Excitation Parameters	Polycapillary or Aperture Collimation
Target Materials	Rh (others available)
Tube	50kV, 50W, 1mA (optional 2nd tube)
Spot Size	$\geq 5\text{-}1000\mu\text{m}$
Filters	Up to 8
Geometry	Top-down Beam (Perpendicular)
Detector (s)	SDD
Resolution	130-145eV
Active Area	70-150mm ²
Stage	Motorized X,Y,Z Up to 600x300mm ranges available
Sample Travel	Total 600x300x150mm
Map Mapping	400x300mm
Map Scan Speed	1-3ms/pixel
Sample Speed	up to 300mm/second
Sample View	Three Sample Positioning and Analysis Cameras
Instrument Control	PC; Windows 10 or 11 Complete control of parameters, filters, cameras, optical microscopes, sample illumination and positioning, and measurement media
Power	100-240 V, 50/60 Hz
Certifications	CE, RoHS, Radiation
Element Range	Na-U, C-U with LE configuration
Dimensions	67x31x64in (1690x787x1630mm)
Safety	Radiation < 1 $\mu\text{Sv/h}$

ATLAS M TECHNICAL SPECIFICATIONS

Sample Types	Solids, Liquids, Particles, Powders
Sample Chamber Size	20x18x10in. (508x457x254mm)
Measurement Media	Air, Vacuum, He
Excitation Source	Primary 50W / 50kV / 1mA Secondary 4W-12W / 40kV / 0.4mA-1mA
Excitation Parameters	Polycapillary or Aperture Collimation
Target Materials	Rh (others available)
Tube	50kV, 50W, 1mA (optional 2nd tube)
Spot Size	$\geq 5\text{-}1000\mu\text{m}$
Filters	Up to 8
Geometry	Top-down Beam (Perpendicular)
Detector (s)	SDD
Resolution	130-145eV
Active Area	70-150mm ²
Stage	Motorized X,Y,Z 25x25mm up to 320x320mm ranges available
Sample Travel	Total 320x320x120mm
Map Mapping	220x200mm
Map Scan Speed	1-3ms/pixel
Sample Speed	up to 300mm/second
Sample View	Three Sample Positioning and Analysis Cameras
Instrument Control	PC; Windows 10 or 11 Complete control of parameters, filters, cameras, optical microscopes, sample illumination and positioning, and measurement media
Power	100-240 V, 50/60 Hz
Certifications	CE, RoHS, Radiation
Element Range	Na-U, C-U with LE configuration
Dimensions	35x22x22in (890x560x560mm)
Safety	Radiation < 1 $\mu\text{Sv/h}$



IXRF, Inc.
10421 Old Manchaca Rd.,
Ste. 620 Austin, TX 78748 USA



P: +1 512.386.6100
F: +1 512.386.6105
E: info@ixrfsystems.com

www.ixrfsystems.com

